

Heat Pressed Cuttable Material  
I N F O R M A T I O N & I N S T R U C T I O N S

Last Updated: September 2004

Recommended Applications

- Cotton, Polyester, Poly/Cotton Blends, 100% Nylon

Characteristics

- Extra wide roll 20" (50cm)
- Can be washed at up to 104°F (40°C)
- Appropriate for the production of finely detailed logos, numbers, lettering and designs
- Manufactured on a sticky backing for easy weeding and application - if any part of the image lifts up, it can be easily repositioned
- Produces an image with a smooth matte finish - can be ironed after application
- Works well with a pique weave
- Can be applied over other MultiCut materials to produce a multi-color print image

Application

- Remove the protective backing only from ReflectCut before cutting
- Position ReflectCut in cutter with matte side up
- Graphic file for cutting should be mirror imaged
- Weed out unwanted area with weeding tool or exacto knife after cutting
- When applying to nylon always preheat the fabric for 15 seconds before application
- Position weeded ReflectCut on fabric
- Set heat press at 300°F (150°C)
- Press film with light to medium pressure for 15 seconds at 300°F (150°C)
- Release clear film when transfer is cold
- When using other MultiCut materials to produce multi-color designs, place the second color sticky side down over the original (previously applied) and cover the whole transfer with silicon paper or with the mylar peeled on the original press (silicon paper is sold separately - per sheet or non-waxed craft paper can also be used)
- Silicon paper can be reused until it turns brown

Washing Instructions

- Machine washable up to 104°F (40°C)
- Can be hand ironed
- Do not dry clean or tumble dry

Technical Support #1-800-565-5686/(604)320-1803 Fax# 1-800-565-5622/(604)320-1833  
E-Mail: [info@jotopaper.com](mailto:info@jotopaper.com) Web Site: [www.jotopaper.com](http://www.jotopaper.com)